




İMALATIMIZ

OUR MANUFACTURE

MELANJÖR OMLJ 800

Melanjörler köpük konsantresini ayarlı bir şekilde sabit ve seyyar hortum hattına takmak için dizayn edilmiştir. Venturi sistem melanjör içerisinde vakum oluşturur ve köpük konsantresi vakum hortumu vasıtasıyla emilir. Melanjör yatay ve dikey kullanılabilir. Melanjörlerin gövdesi ve modülü paslanmaz çelik (ASTM 304-316-316L) diğer aksamaları delrinden mamüldür. Melanjörler deniz suyu da dahil her türlü su ile çalışır pas ve korozyona yüksek dirençlidir.

INDUCTOR (FOAM MIXER) OMLJ 800

The foam inductors are designed to feed foam concentrate at a set mixing rate into flexible and portable hose line. The venture system creates a vacuum in the body of the inductor and the foam concentrate is picked up via a suction hose inductors can be used horizontal and vertical inductors module and body are made of stainless steel (ASTM 304-316-316L) and other parts are delrine inductors are works with all kinds of water including sea water, without rust and corrosion.

Menşei	Türkiye
Markası	Orifis
İşlevi	Köpük Oranlayıcı
Kodu	MI-008
Bağlantısı	2,1/2" Dişli ve Storz & Flanş
Uzunluk (mm)	300
Genişlik (mm)	77
Yükseklik (mm)	150
Ağırlık (gr)	3580
Akış Oranı (lt/dak)	800 lt/dak.
Çalışma Basıncı	4-12 bar
Azami Basınç	16 bar
Test Basıncı	40 bar
Standart	EN: 13565 - I + A I

Origin	Türkiye
Trademark	Orifis
Function	Foam Inductor
Code	MI-008
Connection	2,1/2" threaded and Storz & Flange
Length (mm)	300
Width (mm)	77
Height (mm)	150
Weight (gr)	3580
Flow rate (l / min.)	800 - lpm
Work Pressure	4-12 bar
Max. Pressure	16 bar
Test Pressure	40 bar
Standart	EN: 13565 - I + A I